

In-Line Splice Kit

DESCRIPTION

The range of cast resin straight joints are approved in accordance with DIN EN 50393 (VDE 0278:393):2006-11, and are suitable for use with both armoured and un-armoured cables up to and including 1kv. The joints are suitable for use on most cable types, including PILC, XLPE, PVC and EPR, and can be supplied complete with armour earth kit and mechanical connectors as standard.

The standard straight joints can be upgraded to suit 3.3kv by using a separate supplementary kit. Designed for armoured cables to allow plenty of room to work.

FEATURES

- Type tested according to: EN 50393:2006-11
- Hydrolysis resistant polyurethane resin in a transparent 2 component bag
- Strong transparent shells
- Fully waterproof, no resin leakage
- Cable spacers included
- Complete kit, sealing tape, sandpaper and protective gloves also included
- Installation instructions with clear drawings
- Quick and easy installation
- Connectors and earthing kits available on request
- Type tested according to: IEC 60455-3-8:2013



In-Line Splice Kit



Item number	Description	Cable Diameter (mm)	Dimensions (mm)
CM0	Straight 6 (Injection moulded)	Ø 5 - 20	L200 x Ø35
CM1	Straight 16 (Injection moulded)	Ø 8 - 30	L250 x Ø45
CM2	Straight 25 (Injection moulded)	Ø 10 - 34	L320 x Ø60
CM2.5	Straight 35/70 (Injection moulded)	Ø 26 - 53	L355 x Ø72
CM3	Straight 95 (Injection moulded)	Ø 30 - 48	L450 x Ø75
CM4	Straight 120 (Injection moulded)	Ø 37 - 67	L547 x Ø108
CM5	Straight 185 (Vacume formed)	Ø 62 - 68	L700 x Ø140
CM6	Straight 300 (Vacume formed)	Ø 45 - 70	L800 x Ø160
CM7	Straight 400 (Vacume formed)	Ø 70 - 105	L1345 x Ø155