

# Flush Fink Test Station

## APPLICATION

The Flush Fink® cathodic protection test station and terminal enclosure is a high strength, maintenance free, non-conductive, flush mounted below ground terminal station. It's patented "Bell Jar" design keeps test leads dry even when the enclosure is covered by flood water.

## FLUSH FINK TEST STATION DATA

**CP Test Station :** Watertight Bell, Terminal Board and Housing are made from Makroblend® polycarbonate alloy, one of the worlds toughest plastics. Flush Fink® is impervious to impact, traffic loads and chemical spills common to street usage.

**Colours :** Red, Orange, Yellow, Green, Blue, White, and Black are standard on Flush Fink® and CottPipe®. Any colour is available as an option.

**Hardware :** Standard nickel plated brass or optional stainless steel for guaranteed long service life. Up to 11 terminals accessible from both sides of the board.

**Accessories :** All Flush Fink® terminal boards can accommodate CottShunts® Slide Resistors, Rheostats, CottMeters® (Volt or Amp), Burndy connectors, Cott bonding/shorting straps, Banana Jacks, and lightning arrestors.

**Dimensions :** 5-1/2" (13.97 cms) Diameter x 8" (20.32 cms) height fits 4" schedule 40 pipe.



# Flush Fink Test Station

## FLUSH FINK FEATURES AND LAYOUT INFORMATION

### Features:

#### CP Test Station

Watertight Bell, Terminal Board and Housing are made from Makroblend<sup>®</sup> polycarbonate alloy, one of the worlds toughest plastics. **FLUSH FINK<sup>®</sup>** is impervious to impact, traffic loads and chemical spills common to street usage.

#### Support Post

**COTTPipe<sup>®</sup>** PE (Standard) polyethylene blend has over 20 years of proven durability. **COTTPipe<sup>®</sup>** PC (optional) polycarbonate is available for the toughest applications. Standard length 1 foot - available to 40 feet with Cott's Telescoping Extender.

#### Colors

Red, Orange, Yellow, Green, Blue, White and Black are standard on **FLUSH FINK<sup>®</sup>** and **COTTPipe<sup>®</sup>**. Any color is available as an option.

#### Hardware

Standard nickel plated brass or optional stainless steel for guaranteed long service life. Up to 11 terminals accessible from both sides of the board.

#### Accessories

All **FLUSH FINK<sup>®</sup>** terminal boards can accommodate **COTTShunts<sup>®</sup>**, Slide Resistors, Rheostats, **COTTMeters<sup>®</sup>** (Volt or Amp) Burndy connectors, Cott bonding/shorting straps, Banana Jacks, **ZAP Gard<sup>®</sup>** locking devices, and lightning arrestors.

#### Dimensions

5½" Diameter x 8" height fits 4" schedule 40 pipe.

