

Flush Fink Test Station

APPLICATION

The Flush Fink® cathodic protection test station and terminal enclosure is a high strength, maintenance free, non-conductive, flush mounted below ground terminal station. It's patented "Bell Jar" design keeps test leads dry even when the enclosure is covered by flood water.

FLUSH FINK TEST STATION DATA

CP Test Station: Watertight Bell, Terminal Board and Housing are made from Makroblend[®] polycarbonate alloy, one of the worlds toughest plastics. Flush Fink[®] is impervious to impact, traffic loads and chemical spills common to street usage.

Colours : Red, Orange, Yellow, Green, Blue, White, and Black are standard on Flush Fink[®] and CottPipe[®]. Any colour is available as an option.

Hardware : Standard nickel plated brass or optional stainless steel for guaranteed long service life. Up to 11 terminals accessible from both sides of the board.

Accessories : All Flush Fink® terminal boards can accommodate CottShunts® Slide Resistors, Rheostats, CottMeters® (Volt or Amp), Burndy connectors, Cott bonding/shorting straps, Banana Jacks, and lightning arrestors.

Dimensions : 5-1/2" (13.97 cms) Diameter x 8" (20.32 cms) height fits 4" schedule 40 pipe.





Flush Fink Test Station

FLUSH FINK FEATURES AND LAYOUT INFORMATION

